



MODEL	RG27 Super Jr	RG35 Super Jr
	Gasoline Powered	Gasoline Powered
Weight - lb (kg)	1,770 (803)	1,830 (831)
Length - inches (cm)	114 (290)	114 (290)
Hood Height - inches (cm)	37 (94)	37 (94)
Maximum Height - inches (cm)	52 (132)	52 (132)
Width - inches (cm)	35 (89)	35 (89)
Width with Dual Wheels - inches (cm)	52.5 (133)	52.5 (133)
Ground Drive	Self-Propelled, Variable Speed Hydraulic	Self-Propelled, Variable 2-Speed Hydraulic with High and Low Range
Engine - hp (kW)	27 (20) @ 3600 RPM Vanguard	35 (26) @ 3600 RPM Vanguard
Fuel Tank - gal (L)	6.5 (24.6)	6.5 (24.6)
Clutch	Electromagnetic w/Wheel Brakes	Electromagnetic w/Wheel Brakes
Super Tooth*	18 total	18 total
Cutter Wheel - inches (cm)	17.25 x 1 (43.82 x 3)	17.25 x 1 (43.82 x 3)
Cutting Depth - inches (cm)	12 (30)	12 (30)
Cutting Height - inches (cm)	24.5 (62.2)	24.5 (62.2)
Cutting Width - inches (cm)	51 (130)	51 (130)
Backfill Blade	Optional	Standard

Swing into Action

- 27 hp or 35 hp Vanguard engine
- Flotation tires
- Swing-out control station
- 51" cutting width
- Maintains full depth across entire width of cut



Available with optional hydraulic backfill blade and dual rear wheels (backfill blade standard on the RG35)



51-inch cutting width



Enhanced drive train maximizes cutting power

Think Smart, Think Safe.....

We care about your safety. When operating your RAYCO machinery always wear an approved helmet complete with ear muffs, face shield and the proper eyewear. Never operate under the influence of alcohol or drugs. Know your RAYCO, read and understand your owner's manual cover to cover.